



Technical Data Sheet

MD-Mix Wood

Epoxy Resin Repair Kit

The values are average values. They serve merely for your information, but assume no warranty.

Basis	Epoxy Putty
Color (mixed)	Light wooden
Work life	3 to 4 minutes
Curing time	8 to 10 minutes
Full Strength	24 h
Working temperature	+10°C to +30°C
Shear Strength (DIN 53283) N/mm ²	5,5
Mix rate:	1:1
Shore Hardness D	80
Temperature resistance:	-50 to 180°C (short 300°C)
Shrinking %	ca. 0,05
Thermal Conductivity	0,30 W/m-K
Dielectric capacity	3,0 kV/mm
Gap filling	15

- Fills cracks and holes
- Temperature resistant up to 180°C and up to +300°C for short times
- For on-the-spot repairs



Application:

Useful for repairs for wood products: Planks, Furniture,
Boards & and Plywood, Particle Boards, Wooden
Flooring, Wooden applied products

How to use:

1. Make the application surface clean, dry and free from dust, rust, oil etc.
2. If the surface to be applied is smooth, roughen with sand-paper for better adhesion.
3. Wear protective eye glasses and hand-gloves whenever necessary.
4. Cut the required quantity of putty stick.
5. Mix the putty homogeneously and apply the mixture immediately on the surfaces to be bonded.
6. Apply pressure to hold the surface until the adhesive cures.

Packing units:

24 pcs á 56 g	Art.Nr. MIX.H.56
12 pcs. á 115 g	Art.Nr. MIX.H.115